

Product Name:	SureSeal® 600 Series
Product Type:	One piece, three-ply coextruded liner.
Material:	Polypropylene skin top and bottom with foamed polyolefin core.
Composition:	Core and outer skin fusion. Closed cell foam core of LDPE is sandwiched within polypropylene. This results in a chemically fused, single polymeric product.
Composition Benefits:	Symmetrical construction - either side serves as the liner face. Single polymeric product - no ply-separation.
Application:	Recommended as a secondary liner for heat induction innerseals. Applications have provided positive sealing for food, beverages, pharmaceuticals, cosmetics, industrial, and household chemicals. For US and EU food contact applications. Complies with European Union EC No 1935/2004, meets the compositional requirements of European Union EU No 10/2011*, complies with European Union EC No 2023/2006
Performance Values:	Excellent sealability and resiliency.
Thickness/Width:	Available in thicknesses of .030", .035", and .040" (+/- .005") Widths from 1.25" to 36" (+/- .03125")
Density:	SureSeal®626 = 26 < 30 lbs/ft³ SureSeal® 632 = 32 < 36 lbs/ft³
Color:	Custom colors available upon request.

The information and statements concerning the products as stated in this bulletin are not to be construed as a warranty or representation for which we assume legal responsibility. Empirical testing should be undertaken to determine the suitability for a particular purpose. No warranty of fitness for a particular purpose is made. SureSeal® is a Registered Trademark of J.S. Plastics, Inc. This document is effective from 02/25/2005, revised on 07/26/2024.

*NAIS was not performed.